



# GKMV30P

## Volumetric Cold Potable Water Meters

The world's most successful domestic water meter. The GKMV30P unique design offers an unparalleled blend of accuracy, durability and security.

### FEATURES

- Volumetric rotary-piston principle of measurement ensures registration even at the very lowest rates of flow with maintained accuracy over the flow range
- Unique grooved piston design
- Can be installed in horizontal, vertical or inclined pipelines without affecting accuracy
- The co-polymer resin manufactured body allows its use with absolute confidence where waters with aggressive or dezincification properties exist
- Requires no calibration throughout its lifespan
- 'O' ring seal placed between the measuring chamber and meter body ensures that internal leaks which could by-pass the measuring chamber are eliminated
- Use of advanced engineered plastics for the measuring chamber minimises wear and maintains reliability under all operating conditions
- Large surface area fine filter prevents damage by gathering solid particles. Due to its design, a partially obstructed filter will not affect the meter's accurate registration

### Compliance with standards

Performance figures for the GKMV30P range meet the requirements of the following standards:

- OIML R49
- ISO 4064

### Tamperproof

The GKMV30P offers outstanding resistance to illegal tampering. Its unique conical body-half design means it cannot be disassembled while in service and the mechanically-driven register cannot be interfered magnetically. An individual serial number engraved on each body.

### Optional features

Internal disc-type reverse flow restrictor can be included as an optional feature. This reduces the possibility of water being flow back illegally.

### Register

The register is fully-sealed, liquid-filled, with a simple straight-reading presentation. The number rollers are totally immersed in a non-toxic liquid which acts as a lubricant. The sac attached to the register casing acts as a balancing membrane and ensures the pressure of the liquid in the register is the same as that of the water inside the meter. The register is placed in a window inside the meter body in the direction of flow for easy reading.

### Remote-reading

The GKMV30P operates as a standard meter until the need arises, and then by simply removing a plastic plug and inserting a probe sensor, it can be converted on location whilst still in use without any disconnection, risk of component damage or need to re-calibrate. The pulse provided by the probe can be linked to a remote register or in the longer term, the output can also be interfaced with a module which could be interrogated by a computer or other device. The GKMV30P model is particularly suitable for incorporation in energy management systems.


## Technical Specification:

Specification according to OIML R49 and ISO 4064

R160 flow range (Q3 / Q1)

Class C equivalent


Meter size	DN15		
Meter thread size	G 3/4" A		
Overload flow rate	Q4 ±2%	m <sup>3</sup> /h	3.125
Permanent flow rate	Q3 ±2%	m <sup>3</sup> /h	2.5
Transitional flow rate	Q2 ±2%	m <sup>3</sup> /h	0.025
Minimum flow rate	Q1 ±5%	m <sup>3</sup> /h	0.01562
Starting flow (approximate)		l/h	2
Maximum registration		m <sup>3</sup>	9999.99999
Output pulse		l/pulse	0.5
All models	Head loss at Q3 less than 0.63 bar.		
	Maximum water temperature 50°C. Maximum working pressure 16 bar		



## Physical properties


Meter size		DN15	DN15
Meter diameter	mm	100	100
Meter length	mm	115	165
Length over connectors	mm	200	250
Weight - meter only (approximate)	kg	0.43	0.44

Typical Accuracy Curve



Flow Rate / l/h

Typical Pressure Loss Curve



Flow Rate / l/h

## Installation

Care should be taken during installation to ensure that the meter and its connectors are not subjected to elongation, compression or bending forces. Allowance should be made for expected expansion and contraction of adjacent pipework. High installation stresses may eventually give rise to joint leakage or even permanent damage to the meter or its connections.

PB56-G1(11012022)



We take pride in being **Your Trusted Engineering Partner.**  
Find out more about us at [www.georgekent.net](http://www.georgekent.net)

While George Kent strives to make the content of its marketing materials as timely and accurate as possible, George Kent makes no claims, promises, or guarantees about the accuracy, completeness, or adequacy of, and expressly disclaims liability for errors and omissions in, such materials. No warranty of any kind, implied, expressed, or statutory, including but not limited to the warranties of non-infringement of third party rights, title, merchantability, and fitness for a particular purpose, is given with respect to the content of these marketing materials.

© 2021 George Kent (Malaysia) Berhad. Manufactured under license from Honeywell International Inc. All rights reserved.



**GEORGE KENT (MALAYSIA) BERHAD**  
(195101000005 (1945-X))

George Kent Technology Centre  
1115 Blok A, Jalan Puchong, Taman Meranti Jaya  
47120 Puchong, Selangor Darul Ehsan

Tel : +603-8064 8000 Fax : +603-8061 9926